| Web Images Videos Maps News Shopping Gmail more ▼ | Scholar Preferences Sign in |
|---|---|
| GOOSIC SCHOIS: FPGA synchronization scheduling emulation s Search Advanced Scholar Search | |
| Scholar Articles and patents | Results 1 - 10 of about 503. (0.14 sec) |
| A reconfigurable logic machine for fast event-driven simulation J Bauer, M Bershleyn, I Kaplan, P Proceedings of the 35th, 1998 - portal.acm.org the transfer of variable information between the processor and the FPGA array subcycle timing for the hardware events • It enforces inter-processor lock-step synchronization 7. Limitations Hardware support for event triggers and process scheduling increases the performance of Cited by 32 - Related articles - 8t. Direct - Att 10 versions | psu.sdu (PDF) |
| [PDF] Accelerated logic simulation by using prototype boards 3 Haufe, P Schwarz, T Bemdt, J Große - Design, Automation and Test in, 1998 - Citeseer up, we assume the same simple logical protocol for simulator and hardware synchronization which is 187-201 [6] J. Willis, Z. Li, ZP Lin: Use of Embedded Scheduling to Compile 337-345, Springer Verlag 1996 [24] M. Koch, D. Tavangarian: Einsatz von FPGA zur Akzeleration Clied by 13 - Related stricles - View as STML - Ad 5 versions | psu.edu (PDF) |
| The design of RPM: an FPGA-based multiprocessor emulator K Öner, LA Barroso, S Iman, J Jeong, K Proceedings of the, 1995 - portai aom.org Extending the simulation phase for too long delays the schedule while not guaranteeing a correct any board, inter-processor interrupts, software system reset, a backplane hardware barrier synchronization, and the D7 D6 D5 D4 D3 D2 D1 D0 CCLK Serial Data per each FPGA Gited by .19 - Related articles - All .11 versions | osu.edu (PDF) |
| [PDF] A survey of hw/sw cosimulation techniques and tools H Hübert, A Jantson - Stockholm, Sweden, Thesis work, Royal Institute of, 1998 - Citeseer for the target machine, and the HW can be implemented, eg on a FPGA, or as an ASIC. Final tion between the system components under simulation, and their synchronization. Further timing control mechanisms, ensured by scheduling policies, are considered Cited by 18 - Related articles - View as HTML - ALC versions | pauladu (POF) |
| [CITATION] A simulation environment for core based embedded systems F Pétrot, D Hommais, A Greiner - Simulation Symposium, 1997, 1997 - leeexplore, leee, org Emulation of the hardware on a board, using for ex- ample an FPGA implementation or an The drawback of this approach reside in the synchronization mechanism that needs to communicate from the of the simulation time of a sys- tem is spend in the scheduling of simulation Cited by 17 - Related strictes - 8t. Direct - Alt 3 versions. | |
| An approach to mapping the timing behavior of VLSI circuits on emulators PB Sabet, I. Vuillemin - rsp. 2001 - computer.org communication overhead and the evaluation load [3]. A great emphasis has been specially put on developing different synchronization strategies [4 Obviously, the obtained performance must be balanced by the high cost of such distributed scheduler in terms of FPGA gate Cited by 8 - Related articles - Al 5 versions | |
| [CITATION] An Approach to Mapping the Timing Behavior of VLSI Cifcuks on Emulators PB Sabet - 12th International Workshop on Rapid System, 2001 - IEEE Related articles | |
| [PDF] FAST: An FPGA-based simulation testbed for ATM networks D Saliadis, A Varma - IEEE INTERNATIONAL CONFERENCE ON, 1996 - Citeseer of their inherently serial nature 5]. Communication and synchronization bottlenecks also limit the to four cells per cell-time, bu er them, and schedule the next cell for transmission Programming of the FPGA devices on the board is accomplished through a programming bus Cited by 7 - Related articles - View as HTML - St. Oirect - Ait 8 versions | psu.sdu (PDF) |
| Performance tradeoffs for emulation, hardware acceleration, and simulation GD Peterson - System on chip methodologies and design, 2001 - books.google.com The limited routing available for FPGAs, typically results in lower utilization rates of the computations tpAR Time spent on parallel computations tsYNC Time spent on synchronization fE Frequency to use each of these verification technologies to best meet the schedule and cost Clied by 3 - Related strides | |
| Instruction set emulation for rapid prototyping of SoCs J Schnerr, G Haug, W Rosenstiei and Test in Europe-Volume 1, 2003 - portal.acm.org These steps include, amongst others, a scheduling within blocks and the binding of symbolic For the implementation of these busses the HDL code of the FPGAs has to be The synchronisation between hardware and the emulated software, the handling of bus accesses, and Cand by 7 - Related articles - All 17 versions | osusdu (PDF) |
| Create email alert | |
| G○○○○○○○○S (| |

FPGA synchronization scheduling ei Search

Go to Google Home - About Google - About Google Scholar

©2010 Google